



sugar & sweeteners division













CL RANGE OF BATCH CENTRIFUGALS



Broadbent offer a wide range of batch centrifuges to suit all applications in the sugar, dextrose and sweetener industries. They offer a combination of mechanical simplicity, cleanliness, crystal dryness and full crystal removal. Where high throughputs and class-leading yields on high purity are required Broadbent batch centrifuges are the answer.

Special variants are also available for the chemical industry processing citric acid, nitrates and other free filtering crystalline materials.

# STANDARD FEATURES

- Simple robust mechanical design reducing maintenance time and costs.
- Centrifuge design has been optimised to improve stability when processing variable massecuites.
- Excellent for use in refineries; clean lines, no complex mechanisms located above the basket, reducing the possibility of contamination.
- Compact design with low headroom requirements.
- High performance drive systems available for up to 28 charges per hour.
- Drive motor options: Standard industrial TEFC induction motor (CLX), or Broadbent direct coupled motor (CL).
- Fully automatic advanced PC & PLC control systems allowing easy integration with the plant DCS.
- Programmable cleaning system keeps the centrifuge clean and reduces water consumption.



CL RANGE OF BATCH CENTRIFUGES#				
Model	Basket Capacity kg*	Cycles Per Hour*	Max G	Max Capacity Tonnes/HR*
CL / CLX 1400	1400	28	1100	39.0
CL / CLX1800	1800	28	1100	50.4
CL / CLX2300	2300	28	1000	64.4

<sup>\*</sup>Dependent on massecuite properties and motor inverter rating selected.

<sup>\*</sup>Design subject to change without notice.

# SUPPLYING MARKETS WITH THE HIGHEST QUALITY STANDARDS FOR WHITE SUGAR




CLX1800



Dual Feed Valve System



Floating Plough
Design



# KEY BENEFITS

- Advanced Intuitive Control System.
   Improved functionality with trending, fault finding, advanced communication, remote maintenance, and CCTV camera options.
- Duplex Basket. Corrosion resistant, long life and low inertia. Baskets are fitted with hoops for maximum safety.
- Optimised Washing. Designed to reduce water consumption per cycle, giving greater sugar yields.
- Floating Plough. Removal of all sugar, reducing the need for screen wash, and allowing faster plough time giving more cycles per hour.
- Sugar Discharge Valve. Large open area with downward opening tight shut off valve.
- Spherical Support Bearing. Provides
   positive location with long life, plus
   lubricant and maintenance free operation.
- Excellent Stability. Proven ability to process variable massecuite.



#### sugar & sweeteners division

#### Thomas Broadbent & Sons Ltd.

Queen Street South, Huddersfield, HD1 3EA, England Tel: +44 1484 477200 Fax: +44 1484 516142

e-mail: tbs@broadbent.co.uk
Web: www.broadbent.co.uk

## **Broadbent Incorporated**

P.O. Box 185249, 2509 Gravel Drive, Fort Worth, Texas 76118, USA Tel: +1 (817) 595 2411 Fax: +1 (817) 595 0415 e-mail: binc@broadbent-americas.com

#### Broadbent (Thailand) Ltd.

88 Moo 5 T. Muang A. Muangchonburi Chonburi 20130, Thailand Tel: +66 38 399340-1 Fax: +66 38 399342 e-mail: bthai@broadbent-asia.com

### Broadbent Yangzhou (China)

Banqiao Road, Guangling Industrial Park, Yangzhou, Jiangsu, China, 225004 Tel: +86 514 87871962 Fax: +86 514 87242655 e-mail: bchina@broadbent-asia.com

#### Broadbent India Private Ltd.

Awfis 4th Floor GK Mall Pimple Saudagar Pune, India 411027 Tel: +91 907 556 7355 e-mail: tbs@broadbent-india.com

#### Industrial Process Division

Tel: +44 1484 477260 Fax: +44 1484 428041 e-mail: ipd@broadbent.co.uk Web: www.broadbent.co.uk

#### Laundry Systems Division

Tel: +44 1484 477243 Fax: +44 1484 516142 e-mail: bls@broadbent.co.uk Web: www.broadbent.co.uk

## Sugar & Sweeteners Division

Tel: +44 1484 477230 Fax: +44 1484 423159 e-mail: sugar@broadbent.co.uk Web: www.broadbent.co.uk

## Service & Spares Division

Tel: +44 1484 477200 24hour: +44 7800 685219 Fax: +44 1484 431821 e-mail: bcsl@broadbent.co.uk Web: www.broadbent.co.uk